


# MXA80 integrated audio system

- The MXA80 has a compact footprint and full functionality plus support for DSD and DXD digital music files thanks to an advanced digital-to-analog converter (DAC).
- Features a 50 watt stereo amplifier and a pair of specially designed 2-way desktop speakers that achieve a remarkably rich and full bodied level of performance for their size.
- 6 inputs – 4 digital and 2 analog – allow you to connect a variety of your music sources.
- USB input accepts PCM signals up to 32-bit/384kHz and supports DSD64, DSD128 and DSD256 along with DXD 352.8kHz and DXD 384kHz.
- Combine it with the similarly-sized MB50 Streaming Audio Player to form the basis of a complete audio system.
- Offers a secure DSD connection for playback of SACDs when paired with the McIntosh MCT450 SACD/CD Transport.
- 5 step Bass Boost Control for further customization.



Compact Yet Full Functionality

**McIntosh**<sup>®</sup>

LEGENDARY PERFORMANCE™

[www.mcintoshlabs.com](http://www.mcintoshlabs.com)

# MXA80 integrated audio system

## AMPLIFIER SPECIFICATIONS

### Amplifier Power Output:

50 watts per channel with both channels operating into 8 Ohms

### Total Harmonic Distortion:

0.005% maximum from 20Hz to 20kHz

### Inputs:

1 high level unbalanced (stereo)  
1 high level balanced (stereo)  
4 digital (see Digital Section)

### Outputs:

1 set of stereo speaker terminals  
(8 Ohms)  
1 headphone (1/4")  
1 preamplifier (stereo)

### Digital Section:

1 Coax  
1 Optical  
1 MCT  
1 USB input accepts PCM signals up to 32-bit/384kHz and supports DSD64, DSD128 and DSD256 plus DXD 352.8kHz and DXD 384kHz  
McIntosh Digital Engine is 32-bit/384kHz,  
USB 2.0 asynchronous

### Tone Controls:

5 Step Bass Boost Control

### Headphone Power Output:

High Selection: 1W  
Normal Selection: 250mW

### Headphone Output Impedance:

8-40, 40-150 and 150-600 Ohms

## LOUDSPEAKER SPECIFICATIONS

### Driver Complement (per speaker):

One 4 inch Woofer/Midrange  
One 3/4 inch Dome Tweeter

### Frequency Response:

60Hz - 45kHz

### Crossover Frequency:

2,000Hz

## GENERAL SPECIFICATIONS

### Overall Dimensions (W x H x D):

23-1/4" (59.1cm) x 10-7/8" (27.62cm) x 19" (48.3cm) including knobs, connectors and cables

### Weight:

50 lbs (22.6 kg) net,  
66 lbs (29.9 kg) in shipping carton



### For the Consumer's Protection:

In order to ensure the highest level of customer satisfaction, new McIntosh products may only be purchased from an Authorized McIntosh Dealer; and, with certain limited exceptions may only be purchased over-the-counter or delivered and installed by the Authorized McIntosh Dealer. McIntosh does not warrant, in any way, products that are purchased from anyone who is not an Authorized McIntosh Dealer, or that have had their serial numbers altered or defaced.



## Companion Products

The MB50 Streaming Audio Player, MCT450 SACD/CD Transport and MHP1000 Headphones are logical companions for the MXA80 Integrated Audio System. Your Authorized Dealer can provide additional information on other McIntosh product combinations.

To learn more, please call us at 1.800.538.6576.

# McIntosh®

LEGENDARY PERFORMANCE™

www.mcintoshlabs.com