





COMPACT HIGH PERFORMANCE HI-FI LOUDSPEAKER



DALI KUPID | SPECIFICATIONS

Frequency range	63 - 25,000 Hz ±3 dB
Sensitivity	83 dB@1mfor2.83 V
Nominal impedance	4 ohm
Maximum SPL	103 dB
Crossover frequency	2,100 Hz
Crossover principle	2-way
Recommended amplifier power	40 - 120 Watt
High frequency driver	1 x 26 mm soft dome
High frequency diaphragm	Soft woven fabric
Low/Mid frequency driver(s)	1 x 4½ inch
Low/Mid frequency diaphragm	Paper and wood fibre cone
Connection input	Single wire
Enclosure type	Bass reflex
Bass reflex tuning frequency	53 Hz
Recommended placement	Stand/shelf/wall
Recommended distance from rear wall	2.5 - 60 cm 1 - 23.6 inches
Dimensions (H x W x D)	237 x 140 x 195 mm 9.3 x 5.5 x 7.6 inches
Weight incl. grille	2.9 kg 6.4 lb
Shipping weight	7.5 kg (pair) 16.5 lb (pair)
Finishes	Black Ash Walnut Caramel White Golden Yellow Chilly Blue
Accessories (Included)	2x Wall brackets 4x Wall bracket screws 8x Rubber feet 2x Front grilles