

Specifications

Material	Aluminium alloy
Display	6.5" LCD touchscreen
DAC	ES9039 Pro
Audio Processor	XMOS XU316
Storage	4G DDR4 +64G eMMC
SSD Protocol	M.2 2280 NVMe interface*2; Each slot supports up to 4TB SSD
USB Ports	USB3.0*2
Ethernet	RJ-45(10/100/1000Mbps)
SFP Fiber Network	SFP modules need to be purchased separately; Supports single-mode single-fiber, single-mode dual-fiber optical modules, as well as SFP electrical port modules
Wi-Fi 6	2.4G+5G
DAC Decoding	Supports up to stereo DSD512 Native and PCM 768KHz 32-Bit
Music File Formats	DSD(DSF,DFF,SACD ISO Support DST up to DSD512), MP3,APE,WAV,FLAC,AIF,AIFF,AAC,NRG,CUE
Music Services	Tidal、Qobuz、Highresaudio、Deezer、Amazon Music etc.
Music Streaming	Tidal Connect、WebDav、UPnP、DLNA etc.
Bluetooth Input	BT 5.0, supports SBC/AAC
USB-B Audio Input	USB Compatibility: Windows (10,11) , Mac, Android、IOS Supports up to stereo DSD512, PCM 768KHz 32Bit
Analog Audio Input	XLR(balanced)+RCA (pre-input) Input range: RCA maximum 2.5Vrms, XLR maximum 5Vrms
Optical/Coaxial Input	Supports up to stereo PCM 192KHz 24Bit, DSD64 Dop
ARC Input	Supports up to stereo PCM 192KHz 24Bit
Optical/Coaxial Output	Supports up to stereo PCM 192KHz 24Bit 、 DSD64 Dop
USB Audio Output	Supports up to stereo DSD512 Native、 PCM 768KHz 32Bit (Only supports DAC audio devices compliant with UAC standards.)
Analog Audio Output	XLR(balanced)+RCA (pre-output)
Control Methods	On-screen touch control, Android/iPhone/iPad APP control, remote control
Analog Audio Characteristics	Output Level: XLR 4.2 V; RCA 2.1V Frequency Response: 20Hz~20KHz XLR/RCA(± 0.15 dB) THD+N: XLR: <0.000078%(-122dB)/RCA :<0.00009%(-121dB) Dynamic Range: XLR > 130dB/RCA > 129dB SNR: XLR >130dB/RCA >129dB Crosstalk: XLR>-123dB/RCA>-122dB
Power Supply	AC 110~240V 50/60Hz Rated Power: 30W
Packing List	Power Cable*1,Trigger Cable*1,RemoteControl*1, Antenna*3,User Manual*1