



Loewe **klang sub1**

Active subwoofer to complement the TV

Active wireless subwoofer for the living room

160 watts total music power with two active 4" drivers and four passive 4" radiators

Hexagonal, point-symmetrical design for compensation of moving masses

360° design with painted acrylic glass plate and special acoustic fabric

Absolutely free of vibration and oscillation

Perfect match for any stereo TV set with variable line-out

Bluetooth with Qualcomm aptX Low Latency

High quality and latency-free wireless signal transmission



Qualcomm aptX
low latency



LOEWE. was found by the brothers Loewe as Radio Frequenz GmbH in Berlin in 1923.

Today we still design, develop and produce consumer electronics – Made in Germany.

bild – is the German word for picture or image.

klang – is the German word for sound or tone.

Data sheet

Loewe **klang sub1**

April 2023

LOEWE.

loewe.tv     

Loewe **klang sub1**

Active subwoofer to complement the TV



Strong companion.

Loewe klang sub1 fits perfectly with all Loewe TV sets and can be connected wirelessly via the transmitter with any TV model - also from any other manufacturer - with variable audio line out, in order to upgrade from stereo to a 2.1 sound solution setup.


Powerful sound.

The arrangement of two 4" active drivers and four 4" passive radiators with 160 watts total music power create a perfect bass foundation for the TV integrated stereo speakers.


Premium Design.

Hochwertige, ausgewählte Materialien, das spezielle Akustikgewebe sowie die Deckplatte aus lackiertem Acrylglas sorgen für den anspruchsvollen und eleganten Look

klang sub1 transmitter



Colour



basalt grey

Model

klang sub1

Article no.

60610



All product and company names are trademarks™ or registered® trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them.

Technical data

Loewe klang

sub1

Audio	
Acoustic speaker concept	closed + passive membranes
Channel configuration (speaker layout)	0.1 (subwoofer)
Output (watts sine / music)	80 / 160
Driver (active + passive)	6 (2x 4" + 4x 4")
Orientation front / side / up / rear firing	radial (motion compensation)
2-channel crossover	● low pass
Class-D amp	●
Frequency range (Hz)	40-100
Individual bass and treble control / Loudness	● (gain adjustment) / —
Multimedia	
Multiroom audio support	—
Multichannel home cinema support	● (stereo + sub)
Connectivity and Interfaces	
Bluetooth	● (aptX Low Latency)
Wireless Digital Audiolink (second generation)	—
Analogue audio in (3.5 mm jack)	● (line in)
Network	
WLAN (Wi-Fi) standard	5.0
WLAN (Wi-Fi) power (max. mW)	<10
WLAN (Wi-Fi) frequency range	2.4 GHz
WLAN (Wi-Fi) encryption	A2DP, SNK, AVRCP
Energy	
Mains voltages AC	100-240V, 50/60 Hz
Power consumption standby / network standby (watts)	<0.5 / <0.5
Environment	
Ambient temperature while in operation	5-35° C
Relative humidity (non-condensing)	20-80%
Dimensions	
Weight (approx. kg) excl. / incl. standard setup solution	4.6
W* x H x D (approx. cm) without setup solution (* incl. signature flag)	28,7 x 15,8 x 28,7
Scope of Delivery	
Manual / power cord	● / ● + transmitter
Optional accessories	
Selection of recommended setup solutions and audio systems	bild v, bild i, bild c, We. SEE

● = available — = not available

Technical changes and delivery options are subject to change without notice. The product portfolio may be different and might vary depending on the country. Service matters are all handled individually.

Data sheet

Loewe **klang sub1**

April 2023