

# Specifications

Model	Hyphn
Sensitivity (2.83Vrms @ 1m)	86dB
Recommended Amplifier Power (RMS into 4 Ohm, Music Signal)	200 - 1,600W
Continuous Power Handling (RMS into Nominal Impedance, Pink Noise with 6dB Crest Factor)	800W
Nominal Impedance	4 Ohm
Minimum Impedance (20Hz to 20kHz)	3.5 Ohm @ 2.2kHz
Drive Unit Complement	4x 8" RDTIII Bass Driver 6x 2" RDTIII Midrange Driver 1x MPDIII Tweeter
Frequency Response (In-room, -6dB)	18Hz - 60kHz
Maximum Peak SPL (single speaker @1m Z-Weighted)	129dB
System Format	3-Way
Bass Alignment	Bass Reflex
Port Tuning Frequency	25Hz
Crossover Frequencies	350Hz, 3.7kHz
External Dimensions (Inc. plinth) (H x W x D)	1392 x 502 x 520 mm (54 <sup>13/16</sup> x 19 <sup>3/4</sup> x 20 <sup>1/2</sup> " )
Weight (Inc. plinth, ex. packaging)	106.9 kg (235 lbs 10.7 oz)




Scan to learn more about Hyphn or visit [monitoraudio.com/hyphn](https://monitoraudio.com/hyphn)

Monitor Audio Ltd.  
24 Brook Road  
Rayleigh, Essex  
SS6 7XJ  
England  
Tel: +44 (0)1268 740580  
Email: [info@monitoraudio.group](mailto:info@monitoraudio.group)

[monitoraudio.com](https://monitoraudio.com)

©Monitor Audio Ltd. | V1-2023 - Hyphn Brochure

 Read me, keep me or recycle me