

# Roksan Blak versterker USB

|                           |                                                                                                                                                                                                                                                                                                                      |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inputs                    | 3 x RCA line inputs<br>1 x Pair analogue XLR inputs<br>1 x USB type-B input 24/192 & DSD compatible (only operational with 'USB' Version)<br>MM phono input<br>aptX Bluetooth input<br>MM input – gain, 76.75dB@1kHz, input impedance 47k ohm, 150pF<br>Line & XLR inputs – input impedance 24k ohm XLR, 40k ohm RCA |
| Gain                      | @ 1kHz, 8ohm 36,75dB                                                                                                                                                                                                                                                                                                 |
| THD                       | @ 1W, 8ohm, 5kHz < 0.02%<br>@ 12W, 8ohm, 5kHz < 0.035%                                                                                                                                                                                                                                                               |
| Power output              | @ 1kHz, 8ohm > 150W<br>@ 1kHz, 4ohm > 230W                                                                                                                                                                                                                                                                           |
| Frequency response        | @ -3dB, 12W, 8ohm from < 20Hz to more than 80kHz                                                                                                                                                                                                                                                                     |
| Channel balance           | @ 1kHz, 8ohm, 12W better than 0.3dB                                                                                                                                                                                                                                                                                  |
| Cross talk                | @ 1kHz, 8ohm < -104dB                                                                                                                                                                                                                                                                                                |
| S/N                       | @ 1kHz, 8ohm, 1W > 76dB                                                                                                                                                                                                                                                                                              |
| Dimensions                | (H x W x D) 140 x 440 (inc. faceplate) x 309mm / 140 x 400 (chassis) x 309mm                                                                                                                                                                                                                                         |
| Weight                    | 14kg                                                                                                                                                                                                                                                                                                                 |
| Rated Power Consumption   | 480W                                                                                                                                                                                                                                                                                                                 |
| Maximum Power Consumption | 800W                                                                                                                                                                                                                                                                                                                 |